

# OMC-S20



## CONNECTOR HEAT OVEN

# OMC-S20

## Connector Heat Oven

### Features

- easily programmable by user
- simple operation by single push of a button
- detachable ferrule cassette with replaceable groove plate for various cord diameters
- high capacity (24 ferrules 1.25 mm, 20 ferrules 2.5mm or 10 standard SC, FC, ST, FSMA plugs)
- adjustable and very stable cord holder
- heating plate and ferrule holder are made of copper for fast heat transfer and quick cure
- wide temperature range up to 200°C
- CE marking available

### Specifications

- operating temperature range: 40°C - 200°C (104°F - 392°F)
- stable cure temperature: +/- 2°C
- power supply: AC 100/110/230V, 50/60Hz (factory setting)
- power consumption: 150W
- dimension: 350(W) x 230(D) x 130(H) mm
- weight: 6kg

### Ordering information

OMC - S20 - X - XX - XX XX

#### Power supply

- 1 - AC 100/110 V
- 2 - AC 230V

#### Cassette for ferrules/plugs

- 11 - cassette for 20 ferrules 2.5 mm
  - 12 - cassette for 24 ferrules 1.25 mm
  - 13 - cassette for 10 SC, FC, ST plug type connectors
  - 14 - cassette for 16 LC/MU plug type connectors
  - 15 - cassette for 10 FSMA 905 plug type connector
- Custom made cassettes available!

#### Groove plate option

- 09 20 - groove plate for 20 x 0.9 mm cords
  - 09 24 - groove plate for 24 x 0.9 mm cords
  - 09 10 - groove plate for 10 x 0.9 mm cords
  - 09 16 - groove plate for 16 x 0.9 mm cords
  - 20 20 - groove plate for 20 x 2 mm cords
  - 20 24 - groove plate for 24 x 2 mm cords
  - 20 10 - groove plate for 10 x 2 mm cords
  - 20 16 - groove plate for 16 x 2 mm cords
  - 30 20 - groove plate for 20 x 3 mm cords
  - 30 10 - groove plate for 10 x 3 mm cords
- Custom made groove plates available!



Address: OptoCon Slovakia Ltd.,  
Strojnicka 29,  
821 05 Bratislava,  
Slovak republic

Phone: +421 7 582 33 208  
Fax.: +421 7 534 12 511  
Email: [optocon@optocon.sk](mailto:optocon@optocon.sk)  
Web: [www.optocon.sk](http://www.optocon.sk)